

Battery Backup Device



ACCESSORY SOLD SEPARATELY

The smart LCD screen offers real-time monitoring of UPS parameters while shutdown and monitoring software enables UPS and remote device control over your network.

This series will help you equip your office with reliable battery backup and protection from power outages. The series is designed to surmount power quality issues such as voltage fluctuations, over voltage, under voltage and voltage blackouts.

In the event of any common power problems, the PS70 UPS activates to protect all connected critical loads. The PS70 streamlines installation to just a few simple steps, allowing backup power protection right out of the box.

Technical Documentation

Key Specs

- **Available models:** 1000VA, 1500VA
- **Smart LCD display**
- **Primary applications:** home or small office, desktop computers, routers, and switches

**See Ordering Information for model number selection*

Features

- Plug and Play
- USB communications & software CD
- Compact Design

General Technical Specifications

Input Voltage	220/230/240VAC
Input Frequency	50/60Hz
Output Voltage	230VAC
Output Waveform	Sine wave (normal), simulated sine wave (battery mode)
Output Frequency	50/60Hz auto sensing
Output Transfer time	4ms (typical)
Battery type	Sealed, maintenance-free lead acid
Battery Recharge	4-6 hours to 90% capacity
Battery Runtime at 50% load	Up to 10 min
Line cord	6ft, IEC C13 to Schuko
Operating temperature	32-104°F (0-40°C)
Humidity	0-90%
Altitude	11,500 ft above sea level

Ordering Information

MODEL

PS70- 1000

PS70-1500

DPS
1030 Arlington Avenue North
St. Petersburg, FL 33705
Phone: (800) 862-4377
www.DiversifiedPower.com



While every precaution has been taken to ensure accuracy and completeness herein, PEMCO assumes no responsibility, and disclaims all liability, for damages resulting from use of this information or for any errors or omissions. Specifications are subject to change without notice.