


Product Name	Gas-Stop ESOV		
Primary Function	Major Leak Shut-Off		
Fitting/Model Number	GSUSA2		
Gas Type	Propane		
Max Working Pressure	26 Bar (2.6 MPa)		
Pressure Range	0.3 Bar - 16 Bar		
Recommended Pressure Regulator	Propane 30-50 mbar (not to be used with an EFV)		
Flow Rate/Capacity	1.5 kg/h (70 SCFH)	Max Dimensions	l: 99.5mm x w: 48mm x h: 70mm



Inlet - ACME Type-1 2G RH (CGA 791) INT	Outlet - ACME Type-1 2G RH (CGA 791) EXT

Additional Information	Pressure Gauge (Propane 0 - 12 bar)
Approval Reference	CGA 791 & UL 2061 & UL 119
Shut-Off Range	≥ 110% Flow Rate
Materials (exc Gauge)	Brass/Viton/NBR/PC Plastic
Burst Pressure	152 Bar
Melting Temp (body)	890c
Operating Temp	Low: -20c High: 55c
Reset Function	Manual Push



Key Attributes	Packaging
100% Shut-Off	Minor Leak Tester
Visual Pressure Gauge	Manual Reset
5 Year Warranty	
	Carton Size
	20pcs/ctn
	Product Packaging
	Plastic Clamshell + SRT
	Instructions
	Included (EN)
	Heat Seal/Tamper Resist
	Yes